



Talcor Breakout Blue

Product Description

TALCOR BREAKOUT BLUE is an anti-seize compound with a distinctive blue colour with its revolutionary technology, consisting of the new generation of stable anti-weld fillers, highly refined, high viscosity base stocks bound with a high melt complex thickener.

Customer Benefits

Contains no heavy metal fillers or additives. Adhesive and cohesive properties ensure excellent adhesion, even in wet conditions, whilst minimising fling-off. High drop point complex thickener provides excellent pumpability and good stability at high temperatures. Will not build up in thread roots, yet leaves sufficient coverage to extend re-lubrication cycles.

Applications

All drill rod, tubes and flanges that are constantly connected and disconnected, typical of the on-shore drilling industry.

Notes

Due to its chemical formulation Breakout Blue is not recommended for general purpose greasing.

Typical Properties

NLGI Grade	1
AP Product Code	571390
Thickener	Complex Based
Dropping Point °C	265
Base Fluid Viscosity @ 40°C (cSt)	ISO 460
Safe Operating Temperature °C	152
Four Ball EP Test Weld Point (kgf)	400

The information in this bulletin is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. It is the user's obligation to evaluate and use the product safely and to comply with all applicable laws and regulations.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A Chevron company product



September 2012