



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL 2 STROKE SEMI-SYNTHETIC OIL

Product Code 41120

Date: 20/09/2018

DESCRIPTION

XL 2 Stroke Semi-Synthetic Oil is a high performance low smoke two stroke oil formulated with a special low ash additive system. It is pre-diluted with a high flash point solvent to facilitate mixing with petrol at all temperatures.

APPLICATION

Recommended for:

- Two Stroke engines in a wide range of outdoor equipment, including chainsaws, brush cutters, lawn mowers, blower vacs, etc., including heavy-duty operations;
- Air and water-cooled two stroke motorcycle engines and scooters;
- Oil injected two stroke engines where fuel/oil premixing is not required, but is NOT suitable for high performance water-cooled marine outboards.

Mixing rate with unleaded fuel is normally 50:1, however for heavy-duty use the mix rate may be increased to 25:1, except that the machinery manufacturer's recommendation should always be adhered to.

SPECIFICATION

Meets the requirements of:

- API TC
- JASO FC FB
- TISI

CHARACTERISTICS*

SAE Fluidity/ Miscibility Classification (J 1536) Grade F/M 2

TEST	METHOD	TYPICAL VALUE
Colour	Visual	Green
Density 15°C g/cm ³	ASTM D7042	0.8760
Flash Point PMCC, °C	ASTM D92	>100
Pour Point °C	ASTM D97	-12
Sulphated Ash, %wt	ASTM D874	0.10
Kinematic Visc 100°C, cSt	ASTM D7042	9.5
Viscosity Index	ASTM D2270	109
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification