



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL ATF TYPE DEX III

Product Code 30100

Date: 08/08/2018

#### DESCRIPTION

XL ATF Type DEX III is a superior automatic transmission fluid blended from highly refined severely hydrotreated virgin base oils and the highest quality additives to achieve a high viscosity index fluid providing exceptional thermal stability, oxidation resistance and sludge control for longer service life.

#### APPLICATION

Suitable for use in all General Motors 4-speed automatic transmissions, Ford Mercon automatic transmissions and wherever Dexron III or Allison C-4 fluids are specified. It is particularly suitable for use in hydraulic systems where high temperatures are encountered and may also be used as a power steering fluid.

#### SPECIFICATION

XL ATF Type DEX III meets or exceeds the following specifications:

- Allison C-4, TES 389B
- Autotrak II
- BTR 95LE 85LE
- DEX IIIH IIIG IID
- Ford M, XL-12
- TASA
- VCE 97340
- Voith H55.6335.xx
- Volvo 37325 37335
- ZF TE-ML 05L 09L 21L

#### CHARACTERISTICS\*

TEST	METHOD	TYPICAL VALUE
Colour	Visual	Red
Density 15°C, g/cm <sup>3</sup>	ASTM D7042	0.8615
Kinematic Viscosity 40°C, cSt	ASTM D7042	40.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	8.0
Viscosity Index	ASTM D2270	150
Flash Point (COC) °C	ASTM D92	>210
Pour Point °C	ASTM D97	-18
FTIR	ASTM E2412	Match

\*Product data shows typical values and do not represent a specification

**The leader in lubricant technology and manufacturing**