



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL ATF SYNTHETIC-DEX III

Product Code 31140

Date: 08/08/2018

DESCRIPTION

XL ATF Synthetic-DEX III is a fully synthetic, superior automatic transmission fluid blended from highly refined synthetic base oils and the highest quality additives to achieve a high viscosity index fluid providing exceptional thermal stability, oxidation resistance and sludge control for longer service life.

APPLICATION

Suitable for use in all General Motors 4-speed automatic transmissions, Ford Mercon automatic transmissions and wherever Dexron III, II or Allison C-4 fluids are specified. It is particularly suitable for use in hydraulic systems where high temperatures are encountered and may also be used as a power steering fluid.

Typical Applications include:

- Heavy duty automatic transmissions with integral retarders.
- Transmissions of vehicles used for towing.
- Ford A4 LD transmissions in taxis and transit vans.

SPECIFICATION

XL ATF Synthetic-DEX III meets the following specifications:

- Allison TES 389 / TES 295 / C4
- Bentley P/N PY112995PA / P/N 81 22 9 400 272/275
P/N 83 33 0 024 359 / P/N 83 22 0 026 922
- BMW/Mini LA 2634 / ETL 7045E / ETL 8072B
P/N 83 22 0 / 142 516 (Texaco ETL-8072B, N402)
- BTR 5M-52 (Ford 95LE)
- Caterpillar T0-2
- Chrysler ATF's, ATF's + 3+4 / SP111
- Chrysler AS68RC / P/N 05127382AA
- Daimler NAG-2 / (LT71141)
- Esso LT 71141
- Ford BTR 95 LE, WSS-M2C922-A1,
- Ford MERCON® / MERCON® MERCON / FNR5
- General Motors DEXRON® III H / III G / IIIF / II D / IIE / II / T-IV, Dexron® VI
- Honda ATF-Z1
- Hyundai SP-III / SP-II / JWS 3309 / T4 / Red 1K
- Idemitsu K17 / HP

The leader in lubricant technology and manufacturing



XL Lubricants Pty Ltd

ABN 84 131 080 790
 306-318 Abbots Road Dandenong Sth 3175
 P: 03 9799 9559 F: 03 9702 8112
 E: sales@xllubricants.com.au



PRODUCT DATA SHEET

- Isuzu ATF / II / III
- JASO M315 Class 1-A
- JATCO FWD (Texaco N402)
- JATCO Jaguar X Type 2001-2005 / JLM 20238 JLM 20292 / JLM 21044 / WSS-M2C922-A1 / K17 JWS (Aisin Warner) JWS, 3314 / 3317 / 3324
- Kia SP-III / SP-II / SP1V/ Red-1K
- MAN 339A / Z1
- Mazda ATF- M III / F1 / F2 / M-5 / T-IV
- Mercedes Benz 236.3 / 236.5 / 236.6 / 236.7 / 236.8 / 236.9 / 236.91 / 236.10 / 236.11
- Mercedes-Benz 5 Speed 1996-2006 (Shell 3403 M115)
- Mitsubishi Diamond SP-III / SPII / ATF J2
- Nissan Matic-K / Matic-J / Matic-D / Matic-W / 402
- Porsche 3309 / PN 000-043-204-41 / 000-043-205-09 000-043-205-28 / 000-043-304-00 / 999-917-547-00 A2
- Renault Matic D2
- Saab 3309-T-IV / 93 165 147 / AW1
- Shell 3403 M115 / LA2634
- Subaru ATF / ATF-HP
- Suzuki 3314 / 3317
- Texaco ETL-7045E / ETL-8702B / N402
- Toyota T DII / T-IV / T-III / WS
- VOITH H55.6335.XX
- VW G-052-025-A2 / G052-055 / G052-162-A1-A2 / G052 533 / G052-990-A2 / G US 000 162
- Volvo P/N 1161521 / 1161540 / 1161640
- Volvo 97341
- ZF TE-ML 11A / 11B

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Colour	Visual	Red
Density 15°C, g/cm ³	ASTM D7042	0.8480
Kinematic Viscosity 40°C, cSt	ASTM D7042	45.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	9.0
Viscosity Index	ASTM D2270	180
Flash Point (COC) °C	ASTM D92	>210
Pour Point °C	ASTM D97	-60
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification