



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL SYNTHETIC ATF – “DEX VI” TRANSMISSION OIL

Product Code 31150

16/08/2018

DESCRIPTION

ATF – DEX VI Transmission Fluid is a superior synthetic automatic transmission fluid blended from high quality synthetic base oils and the highest quality additives to achieve a high viscosity index fluid providing exceptional thermal stability, oxidation resistance and sludge control for longer service life in the majority of today’s transmissions.

APPLICATION

Suitable for use in the majority of vehicles sold in Australia including all General Motors 4-speed automatic transmissions, Ford Mercon automatic transmissions, in most late model imported vehicle transmissions and wherever Dexron VI fluids are specified.

SPECIFICATION

ATF – DEX VI is suitable for use in the following applications:

- Allison TES 389 / TES 295 / C4
- Bentley P/N PY112995PA / P/N 81 22 9 400 272/275
P/N 83 33 0 024 359 / P/N 83 22 0 026 922
- BMW/Mini LA 2634 / ETL 7045E / ETL 8072B
P/N 83 22 0 / 142 516 (Texaco ETL-8072B, N402)
- BTR 5M-52 (Ford 95LE)
- Caterpillar T0-2
- Chrysler ATF’s, ATF’s + 3+4 / SP111
- Chrysler AS68RC / P/N 05127382AA
- Daimler NAG-2 / (LT71141)
- Esso LT 71141
- Ford BTR 95 LE, WSS-M2C922-A1,
- Ford MERCON® / MERCON® MERCON / FNR5
- General Motors DEXRON® III H / III G / IIIF / II D / IIE / II / T-IV, Dexron® VI
- Honda ATF-Z1
- Hyundai SP-III / SP-II / JWS 3309 / T4 / Red 1K
- Idemitsu K17 / HP
- Isuzu ATF / II / III
- JASO M315 Class 1-A
- JATCO FWD (Texaco N402)

- JATCO Jaguar X Type 2001-2005 / JLM 20238 JLM 20292 / JLM 21044 / WSS-M2C922-A1 / K17 JWS (Aisin Warner) JWS, 3314 / 3317 / 3324 SP-III / SP-II / SP1V/ Red-1K
- Kia 339A / Z1
- MAN ATF- M III / F1 / F2 / M-5 / T-IV
- Mazda 236.3 / 236.5 / 236.6 / 236.7 / 236.8 / 236.9 / 236.91 / 236.10 / 236.11
- Mercedes Benz 5 Speed 1996-2006 (Shell 3403 M115)
- Mercedes-Benz Diamond SP-III / SPII / ATF J2
- Mitsubishi Matic-K / Matic-J / Matic-D / Matic-W / 402
- Nissan 3309 / PN 000-043-204-41 / 000-043-205-09
- Porsche 000-043-205-28 / 000-043-304-00 / 999-917-547-00 A2
- Renault Matic D2
- Saab 3309-T-IV / 93 165 147 / AW1
- Shell 3403 M115 / LA2634
- Subaru ATF / ATF-HP
- Suzuki 3314 / 3317
- Texaco ETL-7045E / ETL-8702B / N402
- Toyota T DII / T-IV / T-III / WS
- VOITH H55.6335.XX
- VW G-052-025-A2 / G052-055 / G052-162-A1-A2 / G052 533 / G052-990-A2 / G US 000 162
- Volvo P/N 1161521 / 1161540 / 1161640
- Volvo 97341
- ZF TE-ML 11A / 11B

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Colour	Visual	Red
Density 15°C, g/cm ³	ASTM D7042	0.8490
Kinematic Viscosity 40°C, cSt	ASTM D7042	30.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	5.7
Viscosity Index	ASTM D2270	160
Flash Point, °C (COC)	ASTM D92	>210
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification