



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbots Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL SYNTHETIC ATF – MULTI VEHICLE TRANSMISSION OIL

Product Code 31230

Date: 06/08/2018

DESCRIPTION

ATF – Multi Vehicle Transmission Oil is a superior synthetic automatic transmission fluid blended from high quality synthetic base oils and the highest quality additives to achieve a high viscosity index fluid providing exceptional thermal stability, oxidation resistance and sludge control for longer service life in the majority of today's transmissions.

APPLICATION

Suitable for use in the majority of vehicles sold in Australia including all General Motors 4-speed automatic transmissions, Ford Mercon automatic transmissions, in most late model imported vehicle transmissions and wherever Dexron IIIH, IIIG, or Allison C-4 fluids are specified.

SPECIFICATION

ATF – Multi Vehicle Transmission Oil is suitable in the following applications:

- Allison TES 389 / TES 295 / C4
- Bentley P/N PY112995PA / P/N 81 22 9 400 272/275
P/N 83 33 0 024 359 / P/N 83 22 0 026 922
- BMW/Mini LA 2634 / ETL 7045E / ETL 8072B
P/N 83 22 0 / 142 516 (Texaco ETL-8072B, N402)
- BTR 5M-52 (Ford 95LE)
- Caterpillar T0-2
- Chrysler ATF's, ATF's + 3+4 / SP111
- Chrysler AS68RC / P/N 05127382AA
- Daimler NAG-2 / (LT71141)
- Esso LT 71141
- Ford BTR 95 LE, WSS-M2C922-A1,
- Ford MERCON® / FNR5
- General Motors DEXRON® III H / III G / IIIF / II D / IIE / II / T-IV, Dexron® VI
- Honda ATF-Z1
- Hyundai SP-III / SP-II / JWS 3309 / T4 / Red 1K
- Idemitsu K17 / HP
- Isuzu ATF / II / III
- JASO M315 Class 1-A
- JATCO FWD (Texaco N402)
- JATCO Jaguar X Type 2001-2005 / JLM 20238 JLM 20292 / JLM 21044 / WSS-M2C922-A1 / K17 JWS (Aisin Warner) JWS, 3314 / 3317 / 3324

- Kia SP-III / SP-II / SP1V / Red-1K
- MAN 339A / Z1
- Mazda ATF- M III / F1 / F2 / M-5 / T-IV
- Mercedes Benz 236.3 / 236.5 / 236.6 / 236.7 / 236.8 / 236.9 / 236.91 / 236.10 / 236.11
- Mercedes-Benz 5 Speed 1996-2006 (Shell 3403 M115)
- Mitsubishi Diamond SP-III / SPII / ATF J2
- Nissan Matic-K / Matic-J / Matic-D / Matic-W / 402
- Porsche 3309 / PN 000-043-204-41 / 000-043-205-09 / 000-043-205-28 / 000-043-304-00 / 999-917-547-00 A2
- Renault Matic D2
- Saab 3309-T-IV / 93 165 147 / AW1
- Shell 3403 M115 / LA2634
- Subaru ATF / ATF-HP
- Suzuki 3314 / 3317
- Texaco ETL-7045E / ETL-8702B / N402
- Toyota T DII / T-IV / T-III / WS
- VOITH H55.6335.XX
- VW G-052-025-A2 / G052-055 / G052-162-A1-A2 / G052 533 / G052-990-A2 / G US 000 162
- Volvo P/N 1161521 / 1161540 / 1161640
- Volvo 97341
- ZF TE-ML 11A / 11B

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Colour	ASTM D1500	1.5
Density 15°C, g/cm ³	ASTM D7042	0.8480
Kinematic Viscosity 40°C, cSt	ASTM D7042	35.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	6.8
Viscosity Index	ASTM D2270	160
Flash point, °C (COC, min.)	ASTM D92	>210
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification