



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL ATF TYPE 95LE

Product Code 30140

Date: 28/08/2018

DESCRIPTION

XL ATF Type 95LE is a semi synthetic automatic transmission fluid blended from highly refined severely hydrotreated virgin base oils and the highest quality additives to achieve a high viscosity index fluid providing exceptional thermal stability, oxidation resistance and sludge control for longer service life.

APPLICATION

Suitable for use in all General Motors 4-speed automatic transmissions, Ford automatic transmissions and wherever Dexron III or Allison C-4 fluids are specified.

SPECIFICATION

XL ATF Type 95LE meets the following specifications:

- Allison C-4, TES 389B
- Autotrak II
- BTR 95LE 85LE
- Caterpillar TO-2
- DEX IIIH IIIG IID
- Ford M, XL-12
- TASA
- VCE 97340
- Voith H55.6335.xx
- Volvo 37325 37335
- ZF TE-ML 05L 09L 21L

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Colour	Visual	Red
Density 15°C, g/cm ³	ASTM D7042	0.8615
Kinematic Viscosity 40°C, cSt	ASTM D7042	37.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	7.2
Viscosity Index	ASTM D2270	162
Flash Point (COC) °C	ASTM D92	>210
Pour Point °C	ASTM D97	-18
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification

The leader in lubricant technology and manufacturing