



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL ENGINE OIL 10W30 SN/CF Peak

Product Code 13145

Date: 09/08/2018

DESCRIPTION

XL Engine Oil 10W30 SN/CF is blended from highly refined severely hydrocracked virgin paraffinic base oils and the highest quality additives, which meets or exceeds the high standards required of this grade of oil to achieve long engine life and less maintenance without sacrificing fuel consumption, delivering lower exhaust emissions and higher specific horsepower whilst extending oil change intervals. It assists engine management pollution control systems to maintain excellent engine cleanliness.

APPLICATION

XL 10W30 SN/CF motor oil is suitable for most multi-valve and fine-tolerance engine/transmission combinations where an oil of this viscosity grade is specified. It contains no friction modifiers and is suitable in wet-clutch applications. Vehicles operating under low temperature conditions will also benefit from the ability of XL Engine Oil 10W30 to be pumped quickly to all moving parts when the engine is first started. Recommended for all Petrol, Diesel and LPG engine vehicles manufactured from 2001 specifying an API 10W30 grade engine oil.

SPECIFICATION

- ACEA A3/B4-12 A3/B3-12
- API SN
- VW 501 01/505 00

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm ³	ASTM D7042	0.8660
Kinematic Viscosity 40°C, cSt	ASTM D7042	70.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	11.5
Viscosity Index	ASTM D2270	160
Flash Point, °C	ASTM D92	>210
TBN, mg KOH/g	ASTM D2896	7.5
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification