



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL ENGINE OIL 10W30 SS SM/CF

*SEMI SYNTHETIC*

Product Code 15140

Date: 09/08/2018

#### DESCRIPTION

XL Semi-Synthetic Engine Oil 10W30 SM/CF is blended from high quality synthetic and hydrocracked mineral base stocks and the highest quality additives, which meets or exceeds the very high standards required of this grade of oil to achieve long engine life and less maintenance without sacrificing fuel consumption, delivering lower exhaust emissions and higher specific horsepower whilst extending oil change intervals. It assists engine management pollution control systems to maintain excellent engine cleanliness.

#### APPLICATION

Recommended for most multi-valve and fine-tolerance engine/transmission combinations where an oil of this viscosity grade is specified. Vehicles operating under low temperature conditions will also benefit from the ability of this oil to be pumped quickly to all moving parts when the engine is first started. Recommended for all Petrol, Diesel and LPG engine vehicles manufactured from 1997 where API SM/CF performance is stipulated or ACEA A3, B3 is specified.

#### SPECIFICATION

Meets the following specifications:

- ACEA A3/B3-12
- ACEA A3/B4-12
- API SN SM
- MB-Approval 229.1
- VW 501 01/505 00

#### CHARACTERISTICS\*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm <sup>3</sup>	ASTM D7042	0.8650
Kinematic Viscosity 40°C, cSt	ASTM D7042	75.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	12.0
Viscosity Index	ASTM D2270	150
Flash Point, °C	ASTM D92	>210
FTIR	ASTM E2412	Match

\*Product data shows typical values and do not represent a specification