



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL ENGINE OIL 15W40 SL/CF

Product Code 12500

Date: 20/09/2018

#### DESCRIPTION

Engine Oil 15W40 SL/CF is a multi-functional 15W40 petrol/diesel crankcase oil blended from high quality base oils and the highest quality additives, which meets or exceeds the requirements of an SL/CF engine oil. It assists in maintaining engine cleanliness in all engines using leaded, unleaded and LPG fuels and provides good anti-wear protection.

#### APPLICATION

Recommended for all Petrol, Diesel and LPG engine vehicles specifying a 15W40 petrol SL grade or a diesel CF grade engine oil, including those vehicles fitted with turbo-chargers. Ideal for use in LPG fueled vehicles and diesel engines where API CF performance is specified.

#### SPECIFICATION

Meets the following specifications:

- ACEA A3/B4-12 A3/B3-12
- API SN SM SL CF
- VW 501 01/505 00

#### CHARACTERISTICS\*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm <sup>3</sup>	ASTM D7042	0.8710
Kinematic Viscosity 40°C, cSt	ASTM D7042	110
Kinematic Viscosity 100°C, cSt	ASTM D7042	14.5
Viscosity Index	ASTM D2270	135
Flash Point, °C	ASTM D92	>210
Phosphorous, max, %wt	ASTM D5185	0.10
FTIR	ASTM E2412	Match

\*Product data shows typical values and do not represent a specification