

PRODUCT DATA SHEET**XL ENGINE OIL 15W40 SM/CF A3/B4**

Product Code 12530

Date: 15/08/2018

DESCRIPTION

XL Engine Oil 15W40 SM/CF A3/B4 is a multi-functional new generation high performance 15W40 petrol/diesel crankcase oil blended from severely hydrocracked virgin base oils and the highest quality additives, which meets or exceeds the requirements of an SM/CF engine oil. It assists in maintaining engine cleanliness in all engines using leaded, unleaded and LPG fuels and provides exceptional anti-wear protection compared to lower specification oils.

APPLICATION

Recommended for all Petrol, Diesel and LPG engine vehicles specifying a 15W40 petrol SM grade or a diesel CF grade engine oil, including those vehicles fitted with turbo-chargers. Ideal for use in LPG fuelled vehicles and diesel engines where API CF performance is specified.

SPECIFICATION

Meets the following specifications:

- ACEA A3/B4-12 A3/B3-12
- API SN SM CF
- VW 501 01 505 00

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm ³	ASTM D7042	0.8740
Kinematic Viscosity 40°C, cSt	ASTM D7042	120
Kinematic Viscosity 100°C, cSt	ASTM D7042	14.0
Viscosity Index	ASTM D2270	130
Flash Point, °C	ASTM D92	>210
TBN, mg KOH/g	ASTM D2896	11.0
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification