



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL ENGINE OIL 15W50 SM/CF

Product Code 12200

Date: 15/08/2018

#### DESCRIPTION

XL Engine Oil 15W50 SM is a multi-functional shear stable motor oil blended from high quality severely hydrocracked virgin paraffinic base oils and industry approved additives, which meets or exceeds the industry requirements of a 15W50 SM engine oil. It assists in maintaining engine cleanliness in all engines using leaded, unleaded and LPG fuels and provides better protection from excessive wear, acid corrosion, excessive piston deposits and provides less oil thickening and sludge deposits compared to lower specification oils.

#### APPLICATION

Recommended for the lubrication of all types of cars, light commercials and diesel engines where an SM petrol rating or CF diesel rating is specified and is also ideal for LPG powered vehicles requiring an SM or CF lubrication rating.

#### SPECIFICATION

Meets the following specifications:

- ACEA A3/B4-12 A3/B3-12
- API SN SM
- PSA B71 2300
- VW 501 01/505 00

#### CHARACTERISTICS\*

TEST	METHOD	TYPICAL VALUE
Density 15°C g/cm <sup>3</sup>	ASTM D7042	0.8710
Kinematic Viscosity 40°C cSt	ASTM D7042	170
Kinematic Viscosity 100°C cSt	ASTM D7042	19.0
Viscosity Index	ASTM D2270	120
Flash Point, °C	ASTM D92	>210
TBN, mg KOH/g	ASTM D2896	7.5
Sulfated Ash %wt	ASTM D874	0.95
FTIR	ASTM E2412	Match

\*Product data shows typical values and do not represent a specification