



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL ENGINE OIL 15W50SS SM/CF ACEA A3/B3

Product Code 15100

Date: 10/08/2018

#### DESCRIPTION

XL Semi-Synthetic Engine Oil 15W50 SM/CF is blended from high quality synthetic and mineral oil base stocks and the highest quality additives, which meets or exceeds the very high standards required of this grade of oil to achieve long engine life and less maintenance without sacrificing fuel consumption, delivering lower exhaust emissions and higher specific horsepower whilst extending oil change intervals. It assists engine management pollution control systems to maintain excellent engine cleanliness.

#### APPLICATION

Recommended for most multi-valve and fine-tolerance engine/transmission combinations where an oil of this viscosity grade is specified. Vehicles operating under low temperature conditions will also benefit from the ability of this oil to be pumped quickly to all moving parts when the engine is first started. Recommended for all Petrol, Diesel and LPG engine vehicles manufactured from 1997 where API SM/CF performance is stipulated or ACEA A3/B3 is specified.

#### SPECIFICATION

Meets the following specifications:

- ACEA A3/B4-12 A3/B3-12
- API SN SM
- PSA B71 2300
- VW 501 01/505 00

#### CHARACTERISTICS\*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm <sup>3</sup>	ASTM D7042	0.8660
Kinematic Viscosity 40°C, cSt	ASTM D7042	135.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	19.0
Viscosity Index	ASTM D2270	155
Flash Point, °C	ASTM D92	>210
FTIR	ASTM E2412	Match

\*Product data shows typical values and do not represent a specification