



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL ENGINE OIL 20W50 SG/CD

Product Code 11500

Date: 16/08/2018

DESCRIPTION

XL Engine Oil 20W50 SG is a multi-functional shear stable motor oil blended from high quality severely hydrotreated and solvent-refined virgin paraffinic base oils and industry approved additives, which meets or exceeds the industry requirements of a 20W50 SG engine oil. It assists in maintaining engine cleanliness in all engines using leaded, unleaded and LPG fuels and provides better protection from excessive wear, acid corrosion, excessive piston deposits and provides less oil thickening and sludge deposits compared to lower specification oils.

APPLICATION

Recommended for the lubrication of all types of cars, light commercials and diesel engines where an SG petrol rating or CD diesel rating is specified and is also ideal for LPG powered vehicles requiring an SG or CD lubrication rating.

SPECIFICATION

Meets the following specifications:

- API SG, SF / CD

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm ³	ASTM D7042	0.8840
Kinematic Viscosity 40°C, cSt	ASTM D7042	170
Kinematic Viscosity 100°C, cSt	ASTM D7042	19.0
Viscosity Index	ASTM D2270	120
TBN, mg KOH/g	ASTM D2896	7.5
Sulfated Ash %wt	ASTM D874	0.95
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification