



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL ENGINE OIL 25W50 SH/CD

Product Code 11100

Date: 15/08/2018

#### DESCRIPTION

XL Engine Oil 25W50 SH is a multi-functional shear stable motor oil blended from severely hydrocracked virgin paraffinic base oils and industry approved additives, which meets or exceeds the industry requirements of a 25W50 SH engine oil. It assists in maintaining engine cleanliness in all engines using leaded, unleaded and LPG fuels and provides better protection from excessive wear, acid corrosion, excessive piston deposits and provides less oil thickening and sludge deposits compared to lower specification oils.

#### APPLICATION

Recommended for the lubrication of all types of cars, light commercials and diesel engines where an SH petrol rating or CE diesel rating is specified and is also ideal for LPG powered vehicles requiring an SH or CE lubrication rating.

#### SPECIFICATION

Meets the following specifications:

- API SH, SG, SF / CE, CD, CC

#### CHARACTERISTICS\*

TEST	METHOD	SPECIFICATION
Density 15°C, g/cm <sup>3</sup>	ASTM D7042	0.8880
Kinematic Viscosity 40°C, cSt	ASTM D7042	170
Kinematic Viscosity 100°C, cSt	ASTM D7042	18.0
Viscosity Index	ASTM D2270	120
Flash Point, °C	ASTM D92	>210
TBN, mg KOH/g	ASTM D2896	7.5
FTIR	ASTM E2412	Match

\*Product data shows typical values and do not represent a specification