



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL ENGINE OIL 25W60 SH/CD

Product Code 11200

Date: 16/08/2018

DESCRIPTION

XL Engine Oil 25W60 SH is a multi-functional shear stable motor oil blended from severely hydrocracked virgin paraffinic base oils and industry approved additives, which meets or exceeds the industry requirements of a 25W60 SH engine oil. It assists in maintaining engine cleanliness in all engines using leaded, unleaded and LPG fuels and provides better protection from excessive wear, acid corrosion, excessive piston deposits and provides less oil thickening and sludge deposits compared to lower specification oils.

APPLICATION

Recommended for the lubrication of all types of cars, light commercials and diesel engines where an SH petrol rating or CD diesel rating is specified and is also ideal for LPG powered vehicles requiring an SH or CD lubrication rating.

SPECIFICATION

Meets the following specifications:

- API SH, SG, SF / CD, CC

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm ³	ASTM D7042	0.8955
Kinematic Viscosity 40°C, cSt	ASTM D7042	280
Kinematic Viscosity 100°C, cSt	ASTM D7042	24.0
Viscosity Index	ASTM D2270	110
Flash Point, °C	ASTM D92	>210
TBN, mg KOH/g	ASTM D2896	7.0
Sulfated Ash %wt	ASTM D5185	0.95
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification