



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL ENGINE OIL 5W40FS SN/CF A3/B4

*FULL SYNTHETIC*

Product Code 14170

Date: 09/08/2018

#### DESCRIPTION

XL Engine Oil 5W40 SN/CF is blended from synthetic base stocks and the highest quality additives, which meets or exceeds the high standards required of this grade of oil to achieve long engine life and less maintenance without sacrificing fuel consumption, delivering lower exhaust emissions and higher specific horsepower whilst extending oil change intervals. It assists engine management pollution control systems to maintain excellent engine cleanliness.

#### APPLICATION

XL 5W40 SN/CF motor oil is suitable for most multi-valve and fine-tolerance engine/transmission combinations where an oil of this viscosity grade is specified. It contains no friction modifiers and is suitable in wet-clutch applications. Vehicles operating under low temperature conditions will also benefit from the ability of XL Engine Oil 5W40 to be pumped quickly to all moving parts when the engine is first started. Recommended for all Petrol, Diesel and LPG engine vehicles manufactured from 2001 specifying an API 5W40 grade engine oil.

#### SPECIFICATION

Meets the following specifications:

- API SN/CF
- ACEA A3/B4-12

#### CHARACTERISTICS\*

| TEST                            | METHOD     | SPECIFICATION |
|---------------------------------|------------|---------------|
| Density 15°C, g/cm <sup>3</sup> | ASTM D7042 | 0.8640        |
| Kinematic Viscosity 40°C, cSt   | ASTM D7042 | 100           |
| Kinematic Viscosity 100°C, cSt  | ASTM D7042 | 15.0          |
| Viscosity Index                 | ASTM D2270 | 155           |
| Flash Point, °C                 | ASTM D92   | >210          |
| Phosphorous, max, %wt           | ASTM D5185 | 0.10          |
| TBN, mg KOH/g                   | ASTM D2896 | 6.6           |
| FTIR                            | ASTM E2412 | Match         |

\*Product data shows typical values and do not represent a specification