



GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790
306-318 Abbotts Road Dandenong Sth 3175
P: 03 9799 9559 F: 03 9702 8112
E: sales@xllubricants.com.au



PRODUCT DATA SHEET

XL GEAR OIL 75W80 GL-4

Product Code 35100

Date: 06/08/2018

DESCRIPTION

XL GEAR OIL 75W80 is a multigrade lubricant containing sophisticated extreme pressure additives designed to give efficient performance in gearboxes and differentials under light and medium load operating conditions.

APPLICATION

XL GEAR OIL 75W80 should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions which specify this grade of gear oil.

SPECIFICATION

XL GEAR OIL 75W80 meets or exceeds the following specifications:

- API GL-4

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm ³	ASTM D7042	0.8500
Kinematic Viscosity 40°C, cSt	ASTM D7042	55.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	9.0
Viscosity Index	ASTM D2270	140
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification