



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL GEAR OIL 75W85 Synthetic GL-4

Product Code 37140

Date: 06/08/2018

#### DESCRIPTION

XL GEAR OIL 75W85 Synthetic Oil is a synthetic multigrade lubricant containing sophisticated extreme pressure additives designed to give efficient performance in gearboxes and differentials under light and medium load operating conditions.

#### APPLICATION

XL GEAR OIL 75W85 Synthetic should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions which specify this grade of gear oil.

#### SPECIFICATION

XL GEAR OIL 75W85 Synthetic meets or exceeds the following specifications:

- API GL-4
- ZF TE-ML 08

#### CHARACTERISTICS\*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm <sup>3</sup>	ASTM D7042	0.8500
Kinematic Viscosity 40°C, cSt	ASTM D7042	55.0
Kinematic Viscosity 100°C, cSt	ASTM D7042	12.0
Viscosity Index	ASTM D2270	140
FTIR	ASTM E2412	Match

\*Product data shows typical values and do not represent a specification