



# GLS T/A XL Lubricants Pty Ltd

ABN 84 131 080 790  
306-318 Abbotts Road Dandenong Sth 3175  
P: 03 9799 9559 F: 03 9702 8112  
E: [sales@xllubricants.com.au](mailto:sales@xllubricants.com.au)



## PRODUCT DATA SHEET

### XL GEAR OIL 75W90 GL-5

Product Code 37130

Date: 06/08/2018

#### DESCRIPTION

XL GEAR OIL 75W90 is a sophisticated, extreme pressure heavy duty automotive multi-purpose gear lubricant designed to meet or exceed the requirements of the API GL-5 service classification. It is fully inhibited against foaming, oxidation and corrosion, and contains sulfur/phosphorous extreme pressure additives which ensure that the oil meets all the requirements of modern automotive differentials, manual transmissions and final drives to operate at high load-carrying capacity at sustained high speed under high torque loading conditions.

#### APPLICATION

XL GEAR OIL 75W90 should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions which specify this grade of gear oil.

#### SPECIFICATION

XL GEAR OIL 75W90 meets the following specifications:

- API GL5 GL4
- MT-1

#### CHARACTERISTICS\*

| TEST                            | METHOD     | TYPICAL VALUE |
|---------------------------------|------------|---------------|
| Density 15°C, g/cm <sup>3</sup> | ASTM D7042 | 0.8610        |
| Kinematic Viscosity 40°C, cSt   | ASTM D7042 | 100.0         |
| Kinematic Viscosity 100°C, cSt  | ASTM D7042 | 16.0          |
| Viscosity Index                 | ASTM D2270 | 150           |
| FTIR                            | ASTM E2412 | Match         |

\*Product data shows typical values and do not represent a specification