

PRODUCT DATA SHEET

XL HYDRAULIC OIL 10

Product Code 60010

Date: 13/09/2018

DESCRIPTION

XL HYDRAULIC OIL 10 is blended from Group 3 base oils and the highest quality Ashless high performance additives, producing a far superior oil compared to conventional mineral base oils, suited to multi-functional applications as hydraulic, circulating and bearing oils; also light gear oils. The premium rust, oxidation and foam inhibitors included, together with superior anti-wear additives and demulsifiers promote excellent cleanliness, longer fluid life, demulsibility and filtering ability even when badly water contaminated. Excellent air release properties minimize compressibility and prevent noisy and erratic operation of equipment. A long charge life is achieved due to the exceptional chemical and thermal stability of the additive components in the finished oil.

APPLICATION

Recommended for the lubrication of a wide range of equipment where high rust and oxidation resistance, anti-wear properties, foam resistance and excellent demulsibility are required. The exceptional performance of the anti-wear additives in the important areas of high-speed / high-pressure pump protection, anti-rust and corrosion, thermal and oxidative stability and filtering ability provides a cost-effective lubricant which reduces equipment downtime. It is particularly suited to all types of hydraulic systems and pumps operating at high speeds.

SPECIFICATION

HYDRAULIC OIL 10 meets the following high standards:

- AFNOR NF E 48-603
- Denison HF-0 / HF-1 / HF-2
- Denison T-6H20C Hybrid Pump (A-TP-30533)
- DIN 51524 part 2 and 3
- Eaton Vickers I-286-S
- Eaton Vickers M-2950-S
- ISO 11158 (HM, HV)
- MAG IAS (Cincinnati Milacron) P-68-69-70
- SEB 181 222 (HLP)
- US Steel 126, 127 & 136

CHARACTERISTICS*

TEST	METHOD	TYPICAL VALUE
Density 15°C, g/cm ³	ASTM D7042	0.8300
Kinematic Viscosity 40°C, cSt	ASTM D7042	10
Kinematic Viscosity 100°C, cSt	ASTM D7042	3.0
Viscosity Index	ASTM D2270	100
Flash Point, °C	ASTM D92	>220
Pour Point, °C	ASTM D97	-10
FTIR	ASTM E2412	Match

*Product data shows typical values and do not represent a specification